


PBE/PBEK型比例溢流阀

PBE/PBEK TYPE PROPORTIONAL PRESSURE RELIEF VALVES

符号 SYMBOL



PBE型阀是座阀结构的先导式溢流阀，用这种阀，系统压力可随电气输入信号，连续改变，压力的极限由磁铁设定，与电流有关。PBEK型溢流阀，在PBE型溢流阀基础上加装一个弹簧加载的压力溢流阀，提供最高压力保护。

PBE type valve is a pilot operated pressure relief valve with poppet structure, which can change the system pressure continuously by electrical input signal, the pressure limit can be preset by proportional solenoid and may be relative with current. PBEK relief valve in the PBE-based, install a spring loaded pressure relief valve to provide maximum pressure protection.

安装尺寸详见第9页 Installation dimensions refer to page 9

PBE	K	*	10	-	60	/	31.5	Y	/	*	*	*
-----	---	---	----	---	----	---	------	---	---	---	---	---

无代号 = 不带最高压力保护

K = 带最高压力保护

NO code=Without max pressure protection

K=With max pressure protection

无 = 先导式溢流阀

C=带主阀芯组成的先导阀 (通径30)

C=不带主阀芯组成的先导阀

T=作为遥控阀的先导阀

No code=pilot operated pressure relief valve

C=Pilot valve with main spool assembly (NG30)

C=Pilot valve without main spool

T=Pilot operated valve as remote control valve

通径: 10; 20; 30

Size:10;20;30

序列号 60

Series number 60

For further detailed 附加说明

无=丁腈橡胶

V=氟橡胶

No code=NBR seals for petroleum oils

V=FPM seals for phosphate ester

无 = 英制螺纹

2 = 公制螺纹

No code=Inch thread; 2=Metric

Y=内部先导供制油内供外排

XY=内部先导供制油外供外排

Y=Internally piloted/externally drained

XY=externally piloted/externally drained

压力等级 Pressure rating 5=5MPa

10=10MPa

20=20MPa

31.5=31.5MPa

CADIRIRI www.cadiriri.com.br

formularios@cadiriri.com.br (11) 2601-2839 (11)

96393-2796